



POLYFLOOD 3 FLOODLIGHT

Technical Details



Features

Polycarbonate vandal-proof face

Tough machined aluminium housing

Weatherproof to IP68

The Polyflood 3 is a high-powered singlecolour spotlight which uses 3 Luxeon Rebel LEDs.

The unit offers excellent light output for numerous applications including wall lighting, mood and accent lighting, garden and ornamental, bar and club and architectural lighting.

The unit is IP68 rated and has an integral adjustable bracket so can be mounted easily to walls, ceilings and floors.

An On-Board drive version of the Polyflood 3 is also available enabling the unit to be driven from a 12-24V constant voltage supply.

Available in various LED colour combinations, the Polyflood 3 can create any desired mood or effect.

A ground spike is also available for soft ground installations.

Specifications

Lighting Performance		350mA	700mA
Light Source	Luxeon Rebel		
LED Quantity	3		
Lumen Output	324lm	648lm	
Expected Lifetime	50,000+		
Input Data		350mA	700mA
Forward Voltage	10VDC		
Power Supply Type	Constant Current		
Input Connection	Flying Lead		
Operating Details		350mA	700mA
Input Power	3.6W	7.2W	
Ambient Temperature	-10 to +40 Degrees C		
Physical Details			
Mounting Type	Aluminium rotating bracket		
Finish	Matte silver anodising		
Ingress Protection	IP68 @ 1Bar		
Options			
Optics	6, 15, 25, 40 Degrees		
Single Colour Options	Warm White, Neutral White, Cool White, Red, Green, Blue, Amber		

Profile Dimensions

