



POLYFLOOD 6 FLOODLIGHT

Technical Details



Features

Polycarbonate vandal-proof face

Tough machined aluminium housing

Weatherproof to IP68

The Polyflood 6 is a high-powered singlecolour spotlight which uses 6 high-power Luxeon Rebel LEDs.

The unit is IP68 rated and is at home in any indoor or outdoor venue.

The fully adjustable and lockable bracket ensures easy mounting on most surfaces.

An optional ground spike is available for installations in soft ground.

An On-Board drive version of the Polyflood 6 is also available enabling the unit to be driven from a 12-24V constant voltage supply.

Available in various colour combinations, the Polyflood 6 can create any mood or effect that you desire.

Specifications

Lighting Performance		350mA	700mA
Light Source	Luxeon Rebel		
LED Quantity	6		
Lumen Output	648lm	1296lm	
Expected Lifetime	50,000+		
Input Data		350mA	700mA
Forward Voltage	20VDC		
Power Supply Type	Constant Current		
Input Connection	Flying Lead		
Operating Details		350mA	700mA
Input Power	7.2W	14.4W	
Ambient Temperature	-10 to +40 Degrees C		
Physical Details			
Mounting Type	Aluminium rotating bracket		
Finish	Matte silver anodising		
Ingress Protection	IP68 @ 1Bar		
Options			
Optics	6, 15, 25, 40 Degrees		
Single Colour Options	Warm White, Neutral White, Cool White, Red, Green, Blue, Amber		

Profile Dimensions

