



### Features

- On-board driver technology
- Powered by Luxeon Rebel
- Built-in thermal protection

The Polaris is a compact single LED fitting, ideal for in-ground or flush-mounting applications.

Typical applications for the Polaris include decking areas, water features, walkways, residential, hotel and bars, and club environments.

It is also suitable for flush ceiling or canopy lighting applications and is available in various single colours.

Ideal for wet rooms and bathrooms.

Also available as dimmable constant current. Other bezel styles and finishes on request.

**THIS PRODUCT IS TO BE WIRED IN PARALLEL**

### Specifications

#### Lighting Performance

|                   |               |
|-------------------|---------------|
| Light Source      | Luxeon Rebel  |
| LED Quantity      | 1             |
| Lumen Output      | 260lm         |
| Expected Lifetime | 50,000+ Hours |

#### Input Data

|                  |                  |
|------------------|------------------|
| Wattage          | 2W               |
| Drive Voltage    | 12VDC            |
| Power Supply     | Constant Voltage |
| Input Connection | Flying Lead      |

#### Operating Details

|                     |                      |
|---------------------|----------------------|
| LED Drive Current   | 350mA                |
| Ambient Temperature | -10 to +40 Degrees C |

#### Physical Details

|                    |                        |
|--------------------|------------------------|
| Mounting Type      | Glued                  |
| Finish             | Matte silver anodising |
| Ingress Protection | IP67                   |

#### Options

|                       |  |
|-----------------------|--|
| Optics                | Narrow, Medium, Wide   |
| Single Colour Options | Warm White, Neutral White, Cool White, Red, Green, Blue, Amber |

### Profile Dimensions

