





Technical Details

Fea	tures	

On-board driver technology

Powered by Luxeon Rebel

Built-in thermal protection

The Polaris is a compact single LED fitting, ideal for in-ground or flush-mounting applications.

Typical applications for the Polaris include decking areas, water features, walkways, residential, hotel and bars, and club environments.

It is also suitable for flush ceiling or canopy lighting applications and is available in various single colours.

Ideal for wet rooms and bathrooms.

Also available as dimmable constant current. Other bezel styles and finishes on request.

THIS PRODUCT IS TO BE WIRED IN PARALLEL

Specifications		
Lighting Performance		
Light Source	Luxeon Rebel	
LED Quantity	1	
Lumen Output	260lm	
Expected Lifetime	50,000+ Hours	
Input Data		
Wattage	2W	
Drive Voltage	12VDC	
Power Supply	Constant Voltage	
Input Connection	Flying Lead	
Operating Details		
LED Drive Current	350mA	
Ambient Temperature	-10 to +40 Degrees C	
Physical Details		
Mounting Type	Glued or sprung	
Finish	Matte silver anodising as standard 316 stainless available on request	
Ingress Protection	IP67	
Options		
Optics	Narrow, Medium, Wide	
Single Colour Options	Warm White, Neutral White, Cool White, Red, Green, Blue, Amber	

