



Technical Details

LED LIGHTING SPECIALISTS

Features

Polycarbonate vandal-proof face

Tough machined aluminium housing

Weatherproof to IP67

The Polyflood 12 is a very high-powered singlecolour LED floodlight for its size, using 12 highpower BridgeLux LEDs. The Polyflood 12 is IP67 rated and so is at home in any indoor or outdoor application.

The fully adjustable and lockable bracket ensures easy mounting on most surfaces and an optional ground spike is available for installations in soft ground.

Available in various colours, the Polyflood 12 can create any mood or effect that you desire.

Specifications	
Lighting Performance	
Light Source	BRIDGELUX
LED Quantity	12
Lumen Output	4060lm
Expected Lifetime	50,000+
CRI	80
Input Data	
Input Voltage	12VDC
Power Supply Type	Constant Voltage
Input Connection	Flying Lead
Operating Details	
Input Power	38W
Ambient Temperature	-10 to +40 Degrees C
Physical Details	
Mounting Type	Aluminium rotating bracket
Finish	Silver or Black Anodise
Ingress Protection	IP67
Options	
Optics (degrees)	Narrow (12) Medium (30) Wide (80)
Single Colour Options	2700K, 3000K, 4000K, 5600K

Profile Dimensions Ø 150